

Fullpro HT SYN LD 5W-20

New Generation Ford F-Max Tractor Engine Oil



Fullpro HT SYN LD 5W-20, is an ultra high performance synthetic diesel engine oil which is specially developed with Ford Otosan engineers and having exclusive Ford Otosan approval for the new generation low emission Euro VI engines of Ford F-Max tractors.

APPLICATIONS

It is the exclusive first and service filling oil of the new generation Ecotorg Euro VI engines of Ford F-Max tractors produced since the beginning of 2023.

CHARACTERISTICS

- It offers maximum fuel economy.
- New additive technology prolongs the life of exhaust gas after treatment systems such as DPF (Diesel Particulate Filter), EGR (Exhaust Gas Recirculation) and SCR (Selective Catalytic Reduction).
- Its active cleaning feature offers residue and sludge control, so keeps engine parts clean.
- Its superior thermal and oxidation stability maintains its performance during the extended oil drain interval.
- It provides excellent wear protection during cold start-up due to its improved low temperature characteristics.

PERFORMANCES

FORD WSS-M2C219-A1

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,855
Viscosity@ 40°C, mm²/s	ASTM D 445	54,5
Viscosity@100°C, mm²/s	ASTM D 445	9,1
Viscosity Index	ASTM D 2270	148
Flash Point, °C	ASTM D 92	231
Pour Point, °C	ASTM D 97	-30
TBN, mgKOH/g	ASTM D 2896	11,3

OPET.TDS.0415/Rev.02/02.03.2023

Phone: +90 216 522 69 00 Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



^{1/2} **NYİ VE TİCARET A.Ş.** OPET FUCHS MADENI YAĞ Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giris Katı TR 34662 Altunizade/Üsküdar/İSTANBUL



technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET FUCHS MADENİ YAĞ2/2AYİ VE TİCARET A.Ş.PhoOrd. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak PlazaFaxNo: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBULtek

OPET.TDS.0415/Rev.02/02.03.2023

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr

