

FMY FORMULA XLD 5W-30

Ford Trucks Euro VI Synthetic Engine Oil

PRODUCT DESCRIPTION

FMY Formula XLD 5W-30, is an ultra high performance synthetic engine oil which is specially developed for Euro VI engines of Ford Trucks and tested by Ford Engineers. Its special formula provides excellent wear protection, easy cold starting, low oil consumption and extended oil drain interval.

CHARACTERISTICS

- Its specially developed formulation meets all performance needs of Ford Trucks.
- Latest additive technology improves the efficiency of exhaust gas after treatment systems such as DPF (Diesel Particulate filter), EGR (Exhaust Gas Recirculation) and SCR (Selectively Catalytic Reduction) and prolongs the life of these systems.
- Its active cleaning feature offers residue and sludge control, so keeps engine parts clean.
- Its superior thermal and oxidation stability maintains its performance during the extended oil drain interval.
- It offers fuel economy.
- It provides excellent wear protection during cold start-up due to its improved low temperature characteristics.

APPLICATIONS

All Euro VI engines of Ford Trucks.

FORD APPROVAL

FORD WSS-M2C213-A1

PACKAGING AND PART NUMBERS

16 KG 5W/30-M2C213-16KGL 175 KG 5W/30-M2C213-175KGL

FMY.TDS.032/Rev.01/13.04.2018

Moc Koc

Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Esref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

1/2

OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.S. Phone: +90 216 522 69 00 Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,853
Viscosity@ 40°C, mm²/s	ASTM D 445	68,6
Viscosity@100°C, mm²/s	ASTM D 445	11,4
Viscosity Index	ASTM D 2270	160
Flash Point, °C	ASTM D 92	228
Pour Point, °C	ASTM D 97	-42
TBN, mgKOH/g	ASTM D 2896	10,1

HEALTH and SAFETY RECOMMENDATIONS

Waste products must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used products may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

2/2

Moc Koc

OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.S. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Esref Çakmak Plaza No: 32 Giris Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

FMY.TDS.032/Rev.01/13.04.2018

Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr