

Fulllife 15W-40

Optimum Lubrication for High Mileage Vehicles



PRODUCT DESCRIPTION

Fulllife 15W-40, is an engine oil which meets the lubrication requirements of gasoline or diesel engines of high mileage passenger vehicles or light commercial vehicles.

APPLICATIONS

- It is suitable to use in gasoline or diesel engines of passenger vehicles or light commercial vehicles.

CHARACTERISTICS

- Its active cleaning feature controls forming of deposit and sludge, so keeps the engine parts clean.
- Its maintains its lubrication even under extreme operating conditions due to its durable oil film strength.
- It provides superior protection especially in high mileage vehicles.
- Its high viscosity index provides engine to function properly.

PERFORMANCES

- API SL/CF

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,883
Viscosity@ 40°C, mm²/s	ASTM D 445	99,12
Viscosity@100°C, mm²/s	ASTM D 445	13,54
Viscosity Index	ASTM D 2270	137
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 97	-36
TBN, mgKOH/g	ASTM D 2896	7,6

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.