

Fullmax TF-DM1 0W-20

Maximum Fuel Economy For Fiat Diesel or Petrol





Engines

PRODUCT DESCRIPTION

Fullmax TF-DM1 0W-20, is a synthetic engine oil specially developed for the needs of patrol or diesel engines of FIAT passenger cars or commercial vhicles.

APPLICATIONS

- It is suitable to use in Euro 6 diesel engines and 1.0 Firefly patrol engines of FIAT passenger cars or light commercial vehicles, also in 1.5 patrol engine of EGEA Hybrid car.
- It is suitable to use in passenger cars or light commercial vehicles where viscosity and performance level requirements are appropriate.

CHARACTERISTICS

- Its special formula enables exhaust gas after treatment systems to operate efficiently and extends service life of these systems.
- · It provides excellent resistance against sludge and soot formation
- Its improved low viscosity property provides maximum fuel economy.
- Its excellent fluidity during cold weather conditions provides quick lubrication of engine parts during first start up, thus protects the engine against wear.

PERFORMANCES

FIAT 9.55535-DM1

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,844
Viscosity@ 40°C, mm²/s	ASTM D 445	42,7
Viscosity@100°C, mm²/s	ASTM D 445	8,3
Viscosity Index	ASTM D 2270	172
Flash Point, °C	ASTM D 92	226
Pour Point, °C	ASTM D 5950	-45
Total Base Number, mgKOH/g	ASTM D 2896	9,30

1/2

OPET.TDS.0115/Rev.02/02.06.2023



opetfuchs.com.tr



technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0115/Rev.02/02.06.2023



No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 **Fax** : +90 216 522 69 90

teknikservisler@opetfuchs.com.tr opetfuchs.com.tr