

## Arga Super EPX 2

### *Heavy Duty Automotive Grease with Solid Lubricants*

#### PRODUCT DESCRIPTION

**Arga Super EPX 2**, is a multi purpose excellent performance lithium based automotive grease containing molybdenum disulphide (MoS<sub>2</sub>). It has high load carrying capacity and excellent wear protection feature due to extreme pressure (EP) additive. It is recommended for lubrication of camshaft, slideway and other moving machine components have longer re-greasing intervals and exposed to limited, impact or vibrating loads.

#### APPLICATIONS

- It is suitable for components operating under low speed, high and impact load conditions in construction equipment, heavy and light commercial vehicles and passenger vehicles. It is recommended for general lubrication of construction equipment.

#### CHARACTERISTICS

- Provides excellent protection under vibrating and impact loads.
- Its high water wash-out and steam resistance provides longer re-greasing intervals, so reduces cost.
- It gives an outstanding performance even under high loads due to low leakage feature, water wash-out resistance and high oxidation stability
- Its high rust and corrosion protection extends equipments service life.

#### PERFORMANCES

- CNH MAT 3550 Grade C

#### TYPICAL PROPERTIES

##### NLGI

Colour

Soap Type

DIN Classification

ISO Classification

Worked Penetration, 0,1mm  
(25°C, 60 strokes)

Base Oil Viscosity @40°C, mm<sup>2</sup>/s

Base Oil Viscosity @100°C, mm<sup>2</sup>/s

Dropping Point, °C

Operating Temperature, °C

4-Ball Weld Load, N

DIN 51502

ISO 6743-9

ASTM D 217

ASTM D 445

ASTM D 445

ASTM D 566

ASTM D 2596

**2**

Black

Lithium

KPF 2K-30

L-XCCEB-2

265-295

180,0

16,0

>190

-30 to 130

>3200

## HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

*The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.*

*The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.*

*This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.*