

FMY FORMULA FE ULTRA 5W-30

Ultra High Performance Synthetic Engine Oil

PRODUCT DESCRIPTION

FMY Formula FE Ultra 5W-30, is a synthetic fuel economy engine oil which is specially developed for Ford brand passenger cars and light commercial vehicles. It has WSS-M2C913-D approval.

CHARACTERISTICS

- Due to improved special additive package it has Total Base Number (TBN) more than WSS-M2C913-D.
- It has a high thermal stability and offers excellent protection against oxidation.
- It offers excellent residue, soot and deposit control.
- It provides excellent wear protection during cold start-up due to its improved low temperature characteristics.

APPLICATIONS

• It is suitable to use in gasoline or diesel engines of Ford brand passenger cars and light commercial vehicles with or without DPF manufactured in 2011 and after for which Ford recommends using oil with new WSS-M2C913-D approval.

FORD APPROVAL

Ford WSS-M2C913-D

PACKAGING AND PART NUMBERS

Liter	5W/30-M2C913D-1L
Liters	5W/30-M2C913D-4L
Liters	5W/30-M2C913D-7L
Liters	5W/30-M2C913D-10LTP
KG	5W/30-M2C913D-206L
	Liters Liters Liters

FMY.TDS.029/Rev.05/28.01.2019

M Koc

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Phone: +90 216 522 69 00

1/2

Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



TYPICAL PROPERTIES

Density @15°C, g/ml	ASTM D 4052	0.853
Viscosity @40°C, mm²/s	ASTM D 445	54.2
Viscosity @100°C, mm²/s	ASTM D 445	9.7
Viscosity Index	ASTM D 2270	167
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 97	-33
TBN, mgKOH/g	ASTM D 2896	10.3

HEALTH and SAFETY RECOMMENDATIONS

Waste products must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used products may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

2/2

OPET FUCHS MADENI YAĞ SANAYI VE TİCARET A.S. Phone: +90 216 522 69 00 Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giris Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

FMY.TDS.029/Rev.05/28.01.2019

Fax :+90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr