

FMY FORMULA LD 5W-30

Ultra High Performance Synthetic Engine Oil

PRODUCT DESCRIPTION

FMY Formula LD 5W-30 is a ultra high performance synthetic fuel economy engine oil which is specially developed for Euro V diesel engines of Ford Cargo 1846T vehicles. It meets very long oil drain intervals.

CHARACTERISTICS

- It keeps soot and residues finely dispersed and ensures lubrication without problems.
- It prevents deposits in the intake system of turbocharged engines with closed crankcase ventilation.
- It provides fuel economy.
- meets very long oil drain intervals of the orjinal equipment manufacturers.
- It offers easy cold start-up and effective wear protection that may arise during the period till heating of the engine due to its excellent fluidity at low temperatures.

APPLICATIONS

It is suitable to be used in the Euro V diesel engines of Ford Cargo 1846T vehicles.

FORD APPROVAL

FORD WSS-M2C212-A1

PACKAGING AND PART NUMBERS

1 Liter 5W/30-8076-16KGL 5W/30-8076-205L 175 KG

MKoc

FMY. TDS. 023/Rev. 02/13.04.2016

opetfuchs.com.tr



TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0.860
Viscosity@ 40°C, mm²/s	ASTM D 445	71.5
Viscosity@100°C, mm²/s	ASTM D 445	11.9
Viscosity Index	ASTM D 2270	164
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-42
TBN, mgKOH/g	ASTM D 2896	16.4

HEALTH and SAFETY RECOMMENDATIONS

Waste products must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used products may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr

opetfuchs.com.tr