

technical data sheet

Fullgear FD 10W-30

Multi-Purpose Transmission Oil for



Construction Machines

PRODUCT DESCRIPTION

Fullgear FD 10W-30, is a multi purpose transmission oil for manual or automatic transmissions, hydraulic, axle, wet brake systems, final drives, and PTO (Power take Off) of construction machines. Quality base oils and anti-friction additives in their formulation provide high performance while power transmission in moving components.

APPLICATIONS

• It is suitable for use in manual or automatic transmissions, hydraulic, axle, wet brake systems, and PTO of construction machines.

CHARACTERISTICS

- It provides effective protection against high velocity/low torque and low velocity/high torque wear.
- Its high viscosity-temperature behavior enables effective performance even at low temperatures.
- Its anti-friction additives allow the wet brake system to operate efficiently and silently.
- Its specially developed formula provides long service life by controlling rust, corrosion, and foam formation.
- Its high thermal and oxidation stability prevents sludge formation and increases operating efficiency.

PERFORMANCES

- ALLISON C-4
- API GL-4
- CASE MS 1210
- CNH MAT3525
- KUBOTA UDT FLUID
- VOLVO CE WB 101
- ZF TE-ML 17E/06K/05F/03E

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş.PHOrd. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak PlazaFaNo: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBULFa

OPET.TDS.0926/Rev.09/24.01.2024

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



1/2



technical data sheet

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,878
Viscosity@ 40°C, mm²/s	ASTM D 445	58,3
Viscosity@100°C, mm²/s	ASTM D 445	9,8
Viscosity Index	ASTM D 2270	150
Flash Point, ºC	ASTM D 92	224
Pour Point, °C	ASTM D 97	-36

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0926/Rev.09/24.01.2024

MKo<u>c</u>

OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Phone: +90 216 522 69 00 Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr opetfuchs.com.tr