

Fullmax 0W-30

Maximum Protection Under Very Low



Temperatures

PRODUCT DESCRIPTION

Fullmax 0W-30, is a synthetic engine oil that meets the performance requirements of new technology engines. It is especially suitable for gasoline or Ford diesel engines of passenger vehicles and light commercial vehicles. Its special formula provides effective engine cleanliness, superior engine protection, and extreme fuel economy.

APPLICATIONS

- It is suitable for new technology gasoline or diesel engines of passenger vehicles and light commercial vehicles.
- It is especially recommended to be used in diesel engines of high technology vehicles where FORD WSS-M2C950-A performance is required.

CHARACTERISTICS

- It provides excellent wear protection in new generation and high performance gasoline or diesel engines under all operating and driving conditions.
- Its improved friction characteristics provide extreme fuel economy.
- Its superior thermal and oxidation stability maintains its performance during the long oil drain interval recommended by the engine manufacturers.
- · Its excellent fluidity during cold weather conditions provides quick lubrication of engine parts during the first start-up, so it protects the engine against wear.

PERFORMANCES

- ACEA C2
- API SN
- FORD WSS M2C950-A
- LAND ROVER JAGUAR ST JLR.03.5007

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,84
Viscosity@ 40°C, mm²/s	ASTM D 445	46
Viscosity@100°C, mm²/s	ASTM D 445	9,5
Viscosity Index	ASTM D 2270	196
Flash Point, °C	ASTM D 92	230
Pour Point, °C	ASTM D 5950	-45
TBN, mgKOH/g	ASTM D 2896	7,5

OPET.TDS.0112/Rev.03/24.12.2023



OPET FUCHS MADENİ YAĞ SANAYİ VE TİCARET A.Ş. Phone: +90 216 522 69 00

Ord. Prof. Dr. Fahrettin Kerim Gökay Cad. Eşref Çakmak Plaza No: 32 Giriş Katı TR 34662 Altunizade/Üsküdar/İSTANBUL

Fax : +90 216 522 69 90

teknikservisler@opetfuchs.com.tr opetfuchs.com.tr



technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.S. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.



OPET.TDS.0112/Rev.03/24.12.2023

2/2

opetfuchs.com.tr