

# technical data sheet

### Fulltech LD 5W-40

### Ultra-High Performance for Longer oil Drain Interval





#### PRODUCT DESCRIPTION

**Fulltech LD 5W-40**, is a synthetic engine oil that meets the latest performance requirements of modern engines. It is suitable for gasoline or diesel engines of passenger vehicles and light commercial vehicles. Its special formula provides longer drain intervals, effective engine cleanliness, and superior protection.

#### **APPLICATIONS**

Especially for Mercedes Benz and Renault brands, it is suitable to use in passenger vehicles or light commercial vehicles where viscosity and performance level requirements are appropriate.

#### **CHARACTERISTICS**

- It controls the formation of deposits and sludge, so keeps the parts of the engine clean and extends engine life.
- Its superior thermal and oxidation stability preserves its performance during the oil drain interval recommended by the engine manufacturers.
- Its excellent fluidity during cold weather conditions provides quick lubrication of engine parts during the first start-up, so protects the engine against wear.

#### **PERFORMANCES**

- ACEA A3/B4
- API SP
- FIAT 9.55535-N2
- MB-APPROVAL 229.5
- PSA B71 2296
- RENAULT RN 0710/0700
- VW 505 00/502 00

#### **TYPICAL PROPERTIES**

ASTM D 4052	0,85
ASTM D 445	90,2
ASTM D 445	14,5
ASTM D 2270	168
ASTM D 92	230
ASTM D 5950	-39
ASTM D 2896	10,2
	ASTM D 445 ASTM D 445 ASTM D 2270 ASTM D 92 ASTM D 5950

OPET.TDS.008/Rev.05/26.06.2024



1/2



## technical data sheet

#### **HEALTH AND SAFETY RECOMMENDATIONS**

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore, sterilized gloves should always be used. If part of the skin meets used oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specification and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is the responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact Opet Fuchs Technical Services Department for more information.



2/2