

Fulltrac Fluid III 20W-30

Multi-Purpose Tractor Transmission Oil

PRODUCT DESCRIPTION

Fulltrac Fluid III 20W-30, is a multi purpose transmission oil for manuel transmission, hydraulic, axle, wet brake system, final drives and PTO (Power Take Off) of construction and agricultural machines. It minimizes the possibility of brake pads making noise with its friction modifier additive.

APPLICATIONS

It is suitable to use in manuel transmission, hydraulic, axle, wet brake system, final drives and PTO of construction and agricultural machines.

CHARACTERISTICS

- It provides effective protection against high velocity/low torque and low velocity/high torque wear.
- It provides a long service life by keeping rust, corrosion and foam formation under control with its specially developed formula.
- Its anti-friction additives allow wet brake system operates efficiently and silently.

PERFORMANCES

- FORD ESN-M2C86-B
- MASSEY FERGUSON CMS M1135

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,891
Viscosity@ 40°C, mm²/s	ASTM D 445	81,8
Viscosity@100°C, mm²/s	ASTM D 445	9,9
Viscosity Index	ASTM D 2270	99
Flash Point, °C	ASTM D 92	246
Pour Point, °C	ASTM D 5950	-33

1/2





Fax : +90 216 522 69 90 teknikservisler@opetfuchs.com.tr

Phone: +90 216 522 69 00

opetfuchs.com.tr



technical data sheet

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.

OPET.TDS.0803/Rev.11/10.06.2022



Phone: +90 216 522 69 00 **Fax** : +90 216 522 69 90

teknikservisler@opetfuchs.com.tr opetfuchs.com.tr