





Professional range

H.P.L.S.

Transmission Treatment (+ Stop Leak Properties)

Wynn's H.P.L.S. is a manual gearbox treatment which improves gear shifting, lowers gearbox noise and stops oil leaks.

Properties

- ✓ Improves anti-friction and anti-wear properties.
- ✓ Reduces wear caused by metal-to-metal contact (reinforces E.P. additives in gearbox oils).
- ✓ Eases shifting.
- Provides a hydrodynamic lubrication, also under high charges and at high temperature.
- ✓ Prevents and reduces vibration noises of gears and bearings.
- ✓ Lowers cold temperature viscosity to provide immediate lubrication at cold start.
- ✓ Stops and prevents oil leaks.
- ✓ Compatible with all synthetic and mineral based gearbox oils (also ATF Dexron, Mercon) and hydraulic fluids.

Applications

- ✓ For steering gears, manual gearboxes and differentials.
- ✓ Do not use this product in automatic transmissions.

Technical data

Appearance : yellow viscous liquid

Density at 15°C : 0,9188 kg/dm³ Viscosity at 40°C : 580 mm²/s

at 100° C : 74 mm²/s

Flash Point : > 150° C

 $Wynn's \ Belgium \ bvba-Industriepark \ West \ 46-B-9100 \ Sint-Niklaas \ / \ Belgium \ Tel: 32-3-766.60.20 - Fax: 32-3.778.16.56-E-mail: <math display="block"> \underline{mail@wynns.eu} - Website: \underline{www.wynns.eu}$

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.

PN 594XX - Last update: 20/02/2006



Directions

✓ One tube of 125 ml treats 2 litres of gearbox oil.

Packaging

PN 59403 – 24x125 ml tubes – EN/FR/DE/NL/ES/IT/RU/EL/TR/PL/HU/CS PN 59405 – 12x125 ml tubes in blister – EN/FR/DE/NL/ES/IT/RU/EL/TR/PL/HU/CS/SV

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium Tel: 32-3-766.60.20 - Fax: 32-3.778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.

PN 594XX - Last update: 20/02/2006