



TECHNICAL DATA SHEET

INJECTOR CLEANER

PRODUCT DESCRIPTION

Injector Cleaner is a fuel additive for gasoline engines. Control deposit formation in gasoline engines and improves engine efficiency.

USAGE

- First put Injector Cleaner and then add fuel to get the best advance.
- One bottle (300 ml) Injector Cleaner treats up to 50 litres gasoline.

TYPICAL PROPERTIES

Appearance		Light green viscous liquid
Specific Gravity @15°C, kg/lit	ASTM D 4052	0.828
Flash Point, °C	ASTM D 92	78
V.O.C. % Ağ		< 2.0
Inflammableness		Flammable

CHARACTERISTIC/ADVANTAGES

- Its special formula keeps fuel injector system clean.
- Controls and reduce deposit formation in fuel system, combustion chamber and inlet valves.
- Restores power and acceleration.
- Provides smoother idling and reduces noises.
- Prevents resin that occurs in valves at low temperatures.



TECHNICAL DATA SHEET

HEALTH AND SAFETY RECOMMENDATIONS

It is flammable, so must be kept away from fire and sparks. Eye contact should be avoided. In case of eye contact, wash with plenty of water. If contact with skin, wash the area immediately with plenty of water and soap. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.