



## TECHNICAL DATA SHEET

### LPG ECONOMIZER

#### PRODUCT DESCRIPTION

LPG Economizer improves engine oil viscosity index by the high quality additives it contains. Prevents excessive oil consumption especially occurring in old and high mileage vehicles due to wear and reduces engine noises. It is especially developed for engines with LPG.

#### USAGE

- Add to the engine oil while engine is warm.
- 500 ml LPG Economizer treats up to 6 liters of engine oil.

#### CHARACTERISTIC/ADVANTAGES

- Prevents excessive oil consumption occurring due to wear.
- Reduces exhaust smoke.
- Restores compression and improves engine performance.
- Reduces engine noise and wear by forming stable oil film layer between cylinder and piston.

#### TYPICAL PROPERTIES

Appearance		Light blue viscous liquid
Specific Gravity @15°C, kg/lit	ASTM D 4052	0.874
Viscosity @100°C,cSt	ASTM D 445	330
Flash Point, °C	ASTM D 92	220
VOC % Ağ.		0
inflammableness		III B Class



## TECHNICAL DATA SHEET

### HEALTH AND SAFETY RECOMMENDATIONS

It is flammable, so must be kept away from fire and sparks. Eye contact should be avoided. In case of eye contact, wash with plenty of water. If contact with skin, wash the area immediately with plenty of water and soap. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

*The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.*

*The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.*

*This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.*