



TECHNICAL DATA SHEET

DIESEL ANTIFREEZE

PRODUCT DESCRIPTION

Diesel Antifreeze is mixed with diesel fuel to reduce pour point of diesel fuel. It provides engine start up easily by preventing freezing of diesel fuel.

USAGE

- To get best result, first put the Diesel Antifreeze into the fuel tank then add diesel fuel.
- Add 120 litres diesel fuel to the one bottle (330 ml) of Diesel Antifreeze for the optimum mixture.

CHARACTERISTIC/ADVANTAGES

- Reduces freezing point down to -24°C when mixed with the diesel fuel.
- Improves engine performance by helping easy engine start up in cold temperatures.

TYPICAL PROPERTIES

Appearance		Light blue viscous liquid
Specific Gravity @15°C, kg/l		0,823
Viscosity @40°C, cSt	ASTM D 445	2,7
V.O.C. % Weight		<1,0
Inflammableness		II.class



TECHNICAL DATA SHEET

HEALTH AND SAFETY RECOMMENDATIONS

It is flammable, so must be kept away from fire and sparks. Eye contact should be avoided. In case of eye contact, wash with plenty of water. If contact with skin, wash the area immediately with plenty of water and soap. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.