



TECHNICAL DATA SHEET

DIESEL INJECTOR CLEANER

PRODUCT DESCRIPTION

Diesel Injector Cleaner is a fuel additive that cleans fuel system of diesel engines and improves engine performance by controlling deposit formation.

USAGE

- To get best advance, first put the Diesel Injector Cleaner into the fuel tank then add diesel fuel.
- Add 50 litres diesel fuel to the one bottle (330 ml) of Diesel Injector for the optimum mixture.

CHARACTERISTIC/ADVANTAGES

- Rapidly and effectively cleans injector systems of diesel engines.
- Cleans deposits forming at nozzles and inside of the injectors.
- Prevents loss of engine power by cleaning injectors and improves engine performance.
- It can be used both diesel and biodiesel fuel.

TYPICAL PROPERTIES

Appearance		Light brown
Specific Gravity @15°C, kg/l		0,8378
Flash Point, °C	ASTM D 93	85
Inflammableness		Flammable



TECHNICAL DATA SHEET

HEALTH AND SAFETY RECOMMENDATIONS

It is flammable, so must be kept away from fire and sparks. Eye contact should be avoided. In case of eye contact, wash with plenty of water. If contact with skin, wash the area immediately with plenty of water and soap. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.